



PART NUMBERS

308585	1 5-Gallon Pail (Black)
308587	1 50-Gallon Drum (Black)

TECHNICAL DATA

Color	Gray (wet), Black (dry)
Consistency	Low-viscosity liquid
Base	Synthetic latex
Solvent	Water
Weight per Gallon	10.0 lbs (+/- 0.2)
Solids Content	53% (+/-2)
Viscosity	8,500–9,500 cps
Coverage	Up to 530 sq ft/gal (sprayed)
Initial Bonding Time	10 minutes* (5 mils @ RT)
Dry Time	20 minutes* (5 mils @ RT)
Service Temperature	-20°F to 200°F (-28.8°C to 93.3°C)
Surface Burning	Flame spread 0, smoke developed 0 (when tested in accordance with ASTM E84)
Water Resistance	Good
Mildew Resistance	Mold and mildew resistant, contains antimicrobial components
VOC	72 g/l (less water)
Packaging	5-gal pail, 50-gal drum
Freeze/Thaw Stability	Passed 5 cycles

SPECIFICATION/STANDARDS COMPLIANCE

Property	Method	Results
Duct Thermal Insulation	ASTM C916	Pass
VOC Limitation	SCAQMD Rule 1168	Pass
	City of Los Angeles Approval RR #8069	Pass
Surface Burning Characteristics	UL 723	Pass


Booth-Tack is a quick-tack, antimicrobial, nonflammable, water-based insulation adhesive engineered for spray booth applications. Booth-Tack is used in situations when duct insulation is promptly secured by an insulation fastener or the duct section is stored horizontally until the adhesive is dry. Booth-Tack offers high strength, low viscosity, great coverage and low suspended solids.

APPLICATION

Temperature	35°F to 110°F (1.7°C to 44°C)
Method	For use in spray booth operations or specific areas. Booth-Tack may be spray-, brush- or roller-applied to secure insulation to the substrate. Apply according to SMACNA specifications and local codes.
Preparation	Surface must be dry and free of dirt, oil and grease.
Clean Up	UN-TACK™ or Solvent (Use safe handling practices)

STORAGE

Temperature	35°F to 110°F (1.7°C to 44°C)
Shelf Life	One year (unopened)
Flammability	Non-flammable



UNDERWRITERS LABORATORIES, INC.®
 CLASSIFIED ADHESIVE
 Surface Burning Characteristics 294U
 *Applied to inorganic reinforced cement board

FLAME SPREAD..... 0
 SMOKE DEVELOPED..... 0

*Tested as applied in two 3" (76.2 mm)-wide strips 8" (203.2 mm) on center at a coverage of 530 sq ft/gal (13 sq M/L). Flash point of finished adhesive, closed cup: no flash to boiling.

PRECAUTIONS

Inspect all winter shipments upon arrival. Apply when temperatures will not fall below freezing. Do not apply this product in weather-exposed areas or where temperatures will exceed 160°F. Keep out of the reach of children. Review Material Safety Data Sheet for safety information prior to use.

For Industrial Professional Use Only.