

PART NUMBERS

323822	1 Case w/12 14-oz Spray Cans (Black)
--------	--------------------------------------

TECHNICAL DATA

Color	Black
Consistency	Medium–Heavy Spray
Base	Solvent
Solvent	Acetone
Weight Per Gallon	5.80 lbs/gal
Coverage	Excellent
Service Temperature	0°F to 200°F
Dry Time (to touch)	5–10 minutes dependant upon thickness, temperature, humidity & airflow
VOC	<460 g/L
Packaging	14-oz Spray Can

EDGE SEALER is engineered to coat the cut ends of fiberglass duct liner, wrapped insulation, rigid fiberglass duct board and foam insulation. EDGE SEALER's exceptional spray pattern provides complete coverage and encapsulation of exposed insulation.

APPLICATION

Temperature	50°F to 110°F (10°C to 44°C)
Method	Spray on to coat and seal cut edges of fiberglass and foam insulation. Apply according to SMACNA specifications and local codes.
Preparation	Surface must be dry and free of dirt, oil and grease.
Clean Up Dry	UN-TACK™ or Solvent (Use safe handling practices.)

STORAGE

Temperature	35°F to 110°F (1.7°C to 44°C)
Shelf Life	One year (unopened)
Flammability	Extremely Flammable

PRECAUTIONS

Inspect all winter shipments upon arrival. Do not allow this product to freeze. Apply when temperatures will not fall below freezing for the next 36–48 hours. Do not apply this product where temperatures will exceed 200°F. Keep out of the reach of children. Review Material Safety Data Sheet for complete safety information prior to use.

CAUTION: HARMFUL IF SWALLOWED OR INHALED. Avoid breathing vapors. Keep container closed when not in use. Use with adequate ventilation. Wash thoroughly after handling. If swallowed, **DO NOT INDUCE VOMITING.** Call a physician. Overexposure to vapors may cause respiratory irritation. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Contact a physician immediately.

MAY CAUSE SKIN IRRITATION: Prolonged or repeated contact may cause drying, brittleness, cracking or irritation. Use of impervious gloves and clothing recommended. Avoid contact with skin. May be irritating to sensitive skin. Wash thoroughly after handling. In case of contact with skin, remove contaminated clothing and thoroughly wash affected area with soap and water. Do not use if skin is broken. If rash develops, discontinue use. Contact a physician if symptoms persist. **REVIEW MATERIAL SAFETY DATA SHEET FOR COMPLETE SAFETY INFORMATION PRIOR TO USE.**

CONTAINS: Resin and polymer

MAY NOT BE REPACKAGED or sold for other than industrial or professional use.

KEEP OUT OF REACH OF CHILDREN.

For Industrial Professional Use Only.