



OVERVIEW

Carlisle's Low-VOC Un-Tack Adhesive Remover and Cleaner is designed to remove adhesives and primers from a variety of surfaces including sheet metal, accessories, plastic, rubber, and glass. Low-VOC UN-TACK can also be used to clean spray guns and hoses used to apply Hardcast adhesives, as well as removing Hardcast liquid and rolled sealants. Low-VOC Un-Tack is VOC compliant in all 50 states.

PART NUMBERS

330793 (1) #8 Aerosol Cylinder

FEATURES AND BENEFITS

- Clears clogged spray guns and hoses
- Allows easy clean up of excess adhesive and over-spray
- Low VOC formula
- 50-state compliant
- Removes Hardcast liquid and rolled sealants
- Made in USA

SPECIFICATIONS/STANDARDS COMPLIANCE

| Property | Method | Results |
|---------------|--------|----------------------------|
| Color | Visual | Clear |
| Consistency | | Aerosol Spray |
| Odor | | Slight Solvent Scent |
| Coverage Rate | | 250 to 300 ft ² |
| VOC | | 33 g/l |

APPLICATION

| | |
|-------------------------------|---|
| Temperature | 50°F to 100°F (10°C to 38°C) |
| Preparation | Performance will diminish if used below 60°F (15°C). If you experience this, warm cylinder to room temperature. If cylinder freezes, return to room temperature and agitate cylinder. |
| To Clean Up Excess Adhesive | Spray directly on adhesive to be removed and wipe with cloth. Can also spray on cloth and wipe. Wear rubber gloves and goggles when cleaning. |
| To Clear Clogged Guns & Hoses | Lock spray gun trigger. Attach gun and hose to cylinder. Open valve. Allow line to charge. Let system sit. Aim gun away from people, unlock trigger, and spray until clean. Repeat until system is clear. |

PRECAUTIONS

Flammable liquid propellant and vapor. Do not store in direct sunlight. Keep away from open flame. Use with adequate ventilation. Avoid inhalation of spray mist and vapors. Harmful or fatal if swallowed. May cause eye irritation. Keep out of reach of children. Use of goggles and gloves recommended. Cylinders are not refillable and when empty are harmless and disposable. Dispose of according to local codes and laws. Keep cans and cylinders below 100°F (38°C).

STORAGE

| | |
|--------------|---|
| Temperature | 60°F to 100°F (15.5°C to 38°C) DO NOT FREEZE |
| Shelf Life | One year (unopened) |
| Flammability | Flammable |

