



Safety Data Sheet

Material Name: 14 oz Hardcast Edge Sealer LT 12pk

Product #: 323822

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name

14 oz Hardcast Edge Sealer LT 12pk

Synonyms

Sealant

Chemical Family

Solvent Based Sealant

Product Use

Adhesive

Restrictions on Use

For industrial use only

Manufacturer Information

Carlisle HVAC Products
900 Hensley Lane
Wylie, TX 75098
www.carlislehvac.com

Medical Emergency:

CHEMTREC (USA): (800) 424-9300

MSDS Assistance – 972-442-6545
Technical Assistance – 888-229-2199
Customer Service – 888-229-0199

Section 2 - HAZARDS IDENTIFICATION

Classification in accordance with paragraph (d) of 29 CFR 1910.1200.

Flammable aerosols – Category 1
Acute toxicity, inhalation – Category 4
Skin corrosion/irritation – Category 2
Serious eye damage/eye irritation – Category 2A
Sensitization, skin – Category 1
Germ cell mutagenicity – Category 1B
Reproductive toxicity – Category 1A
Specific target organ toxicity, single exposure – Category 3 narcotic effects
Specific target organ toxicity, repeated exposure – Category 2
Aspiration hazard – Category 1

Safety Data Sheet

Material Name: 14 oz Hardcast Edge Sealer LT 12pk**Product #: 323822****GHS Label Elements****Symbol(s)****Signal Word**

Danger

Hazard Statement(s)

Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. May damage fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

Precautionary Statement(s)**Prevention**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Response

If swallowed: Immediately call a poison center/doctor. If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see this label). Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

Storage

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Other Hazards

No additional information available.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent
74-98-6	Propane	20 - 40
107-83-5	2-Methylpentane	10 - 20

Safety Data Sheet

Material Name: 14 oz Hardcast Edge Sealer LT 12pk

Product #: 323822

67-64-1	Acetone	10 - 20
75-83-2	2,2-Dimethylbutane	2.5 - 10
79-29-8	2,3-Dimethylbutane	2.5 - 10
96-14-0	3-Methylpentane	2.5 - 10
115-10-6	Dimethyl Ether	2.5 - 10
71302-83-5	Hydrocarbons, C9-unsaturated, Polymerized	2.5 - 10
108-88-3	Toluene	2.5 - 10
	Other components below reportable levels	10 - 20

Section 4 - FIRST AID MEASURES

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin

Remove contaminated clothing. Wash off with soap and plenty of water. If skin irritation occurs: Get medical advice/attention.

Eyes

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Aspiration may cause pulmonary edema and pneumonitis.

Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically.

Most Important Symptoms/Effects

Acute

Irritation of eyes and mucous membranes.

Delayed

Prolonged exposure may cause chronic effects. May cause drowsiness or dizziness.

Note to Physicians

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. IF exposed or concerned: Get medical advice/attention. Wash contaminated clothing before reuse

Safety Data Sheet

Material Name: 14 oz Hardcast Edge Sealer LT 12pk

Product #: 323822

Section 5 - FIREFIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Powder. Alcohol resistant foam. Water. Carbon dioxide (CO₂).

Unsuitable Extinguishing Media

None known.

Special Hazards Arising from the Chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame.

Hazardous Combustion Products

Extremely flammable aerosol.

Advice for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Firefighting Measures

Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes.

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and Materials for Containment and Cleaning Up

Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Collect spillage. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.

Environmental Precautions

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.



Safety Data Sheet

Material Name: 14 oz Hardcast Edge Sealer LT 12pk

Product #: 323822

Section 7 - HANDLING AND STORAGE

Precautions for Safe Handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Ground and bond containers when transferring material. Do not re-use empty containers. Do not breathe gas. Avoid contact with skin. Avoid contact with eyes. Avoid contact during pregnancy/while nursing. Avoid prolonged exposure. Use only in well-ventilated areas. Use personal protective equipment as required. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash hands thoroughly after handling. Do not empty into drains.

Conditions for Safe Storage, Including any Incompatibilities

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS). Level 3 Aerosol

Incompatible Materials

See Section 10 of the SDS.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

Dimethyl Ether	115-10-6	
ACGIH:	0.3 ppm Ceiling	
NIOSH:	0.1 ppm Ceiling	
OSHA (US):	2 ppm STEL	0.75 ppm TWA
Acetone	67-64-1	
ACGIH:	500 ppm TWA	750 ppm STEL
NIOSH:	250 ppm TWA; 590 mg/m3 TWA	
OSHA (US):	1000 ppm PEL; 2400 mg/m3 PEL	

Safety Data Sheet

Material Name: 14 oz Hardcast Edge Sealer LT 12pk

Product #: 323822

Propane	74-98-6	
NIOSH:	1000 ppm TWA; 1800 mg/m ³ TWA	
OSHA (US):	1000 ppm PEL; 1800 mg/m ³	
Toluene	108-88-3	
ACGIH:	20 ppm TWA	
NIOSH:	100 ppm TWA; 375 mg/m ³ TWA	150 ppm STEL; 560 mg/m ³ STEL
OSHA (US):	200 ppm TWA	300 ppm Ceiling
2,2-Dimethylbutane	75-83-2	
ACGIH:	500 ppm TWA	1000 ppm STEL
2,3-Dimethylbutane	79-29-8	
ACGIH:	500 ppm TWA	1000 ppm STEL
2-Methylpentane	107-83-5	
ACGIH:	500 ppm TWA	1000 ppm STEL
3-Methylpentane	96-14-0	
ACGIH:	500 ppm TWA	1000 ppm STEL

Biological limit value

There are no biological limit values for any of this product's components.

Engineering Controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual Protection Measures, such as Personal Protective Equipment

Eye/face protection

Wear eye/face protection. Wear safety glasses with side shields (or goggles).

Skin Protection

Wear protective gloves.

Respiratory Protection

If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

Safety Data Sheet

Material Name: 14 oz Hardcast Edge Sealer LT 12pk

Product #: 323822

Other

Wear appropriate chemical resistant clothing. Wear appropriate thermal protective clothing, when necessary.

General Hygiene Considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Liquid Aerosol	Physical State	Liquid
Odor	Not available	Color	Not available
Odor Threshold	Not available	pH	Not available
Melting Point	Not available	Boiling Point	76.35° F (24.64° C) estimated
Freezing point	Not available	Evaporation Rate	Not available
Boiling Point Range	Not available	Flammability (solid, gas)	Not available
Autoignition	662° F (350° C) estimated	Flash Point	-54.4° F (-48.0° C) estimated
Lower Explosive Limit	2.2 % estimated	Decomposition	Not available
Upper Explosive Limit	9.5 % estimated	Vapor Pressure	320.86 psig @70° F estimated
Vapor Density (air=1)	Not available	Specific Gravity (water=1)	0.533 estimated
Water Solubility	Not available	Partition coefficient: n-octanol/water	Not available
Viscosity	Not available	Solubility (Other)	Not available
Density	533 g/cm3 estimated (relative)	VOC	55.92 % estimated

Other Information

No additional information available.

Safety Data Sheet

Material Name: 14 oz Hardcast Edge Sealer LT 12pk

Product #: 323822

Section 10 - STABILITY AND REACTIVITY

Reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical Stability

Material is stable under normal conditions.

Possibility of Hazardous Reactions

Hazardous polymerization does not occur.

Conditions to Avoid

Avoid temperatures exceeding the flash point.

Incompatible Materials

Strong oxidizing agents.

Hazardous decomposition products

No hazardous decomposition products are known.

Section 11 - TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation

May be fatal if swallowed and enters airways. Prolonged inhalation may be harmful. Narcotic effects. May cause damage to organs by inhalation.

Skin Contact

Causes skin irritation.

Eye Contact

Causes serious eye irritation.

Ingestion

May be fatal if swallowed and enters airways.

Acute and Chronic Toxicity

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Acetone (67-64-1)

Dermal LD50 Guinea pig >7426 mg/kg, 24 hours

Dermal LD50 Guinea pig >9.4 ml/kg, 24 hours

Dermal LD50 Rabbit >7426 mg/kg, 24 hours

Dermal LD50 Rabbit >9.4 ml/kg, 24 hours

Dermal LD50 Rabbit 20 mg/kg

Inhalation LC50 Rat 557000 ppm, 3 hours

Inhalation LC50 Rat 132 mg/l, 3 hours

Inhalation LC50 Rat 50.1 mg/l

Safety Data Sheet

Material Name: 14 oz Hardcast Edge Sealer LT 12pk

Product #: 323822

Oral LD50 Mouse 3000 mg/kg
Oral LD50 Rabbit 5340 mg/kg
Oral LD50 Rat 5800 mg/kg
Oral LD50 Rat 2.2 ml/kg
Other LD50 Mouse 1297/mg/kg
Other Ld50 Rat 5500 mg/kg

Dimethyl Ether (115-10-6)

Inhalation NOEL Rat 2 ppm, 6 hours
Oral LD50 Rat 460 mg/kg

Hydrocarbons, C9-unsaturated, Polymerized (71302-83-5)

Dermal LD50 Rat >2000mg/kg, 24 hours
Inhalation LC50 Rat >5.14 mg/l, 4 hours
Oral LD50 Rat >16 ml/kg

Propane (74-98-6)

Inhalation LC50 Mouse 1237 mg/l, 120 minutes
Inhalation LC50 Mouse 52%, 120 minutes
Inhalation LC50 Rat 1355 mg/l
Inhalation LC50 Rat 658 mg/l, 4 hours

Toluene (108-88-3)

Dermal LD50 Rabbit >5000 mg/kg, 24 hours
Inhalation LC50 Mouse 6405 – 7436 ppm, 6 hours
Inhalation LC50 Mouse 5320 ppm, 8 hours
Inhaation LC50 Rat 5879 – 6281 ppm, 6 hours
Inhalation LC50 Rat 12.5 – 28.8 mg/l, 4 hours
Oral LD50 Rat 5000 mg/kg

Immediate Effects

Causes damage to central nervous system, body, eyes, systemic toxicity.

Delayed Effects

May damage fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure: eyes, central nervous system.

Irritation/Corrosivity Data

May cause mild skin irritation. May cause mild eye irritation.

Respiratory Sensitization

No data available.

Dermal Sensitization

This product is not expected to cause skin sensitization.

Component Carcinogenicity

Toluene	108-88-3
IARC:	3 Not classifiable as to carcinogenicity to humans.

Safety Data Sheet

Material Name: 14 oz Hardcast Edge Sealer LT 12pk

Product #: 323822

OSHA:	Not listed.
-------	-------------

Germ Cell Mutagenicity

No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Reproductive Toxicity

May damage fertility or the unborn child.

Specific Target Organ Toxicity - Single Exposure

Narcotic effects

Specific Target Organ Toxicity - Repeated Exposure

Respiratory system. Skin. Kidneys. Central nervous system. Eyes. Liver. May cause damage to organs through prolonged or repeated exposure.

Aspiration Hazard

May be fatal if swallowed and enters airways.

Chronic Effects

Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects. May cause damage to organs through prolonged or repeated exposure.

Section 12 - ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected.

Component Analysis - Aquatic Toxicity

Acetone	67-64-1
Invertebrate:	EC50 48 hr Daphnia magna 21.6 – 23.9 mg/l
Fish:	LC50 96 hr Oncorhynchus mykiss 4740 – 6330 mg/l
Dimethyl Ether	115-10-6
Invertebrate:	EC50 48 hr Daphnia pulex 4.3 – 7.8 mg/l
Fish:	LC50 96 hr Morone saxatilis 10.302 – 16.743 mg/l
Toluene	108-88-3
Algae::	IC50 72 hr Algae 433.0001 mg/L
Invertebrate:	EC50 48 hr Daphnia 7.645 mg/L EC50 48 hr Daphnia magna 5.46 – 9.83 mg/l



Safety Data Sheet

Material Name: 14 oz Hardcast Edge Sealer LT 12pk

Product #: 323822

Fish:	LC50 96 hr Oncorhynchus kisutch 8.11 mg/l
-------	---

Persistence and Degradability

No information available for the product.

Bioaccumulative Potential

No information available for the product.

Mobility

No information available for the product.

Other Toxicity

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

Section 13 - DISPOSAL CONSIDERATIONS

Disposal instructions

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

US RCRA Hazardous Waste U List: Reference

Acetone (CAS 67-64-1)	U002
Toluene (CAS 108-88-3)	U220

Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated Packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

Section 14 - TRANSPORT INFORMATION

US DOT

UN number	UN1950
UN proper shipping name	AEROSOLS, flammable

Safety Data Sheet

Material Name: 14 oz Hardcast Edge Sealer LT 12pk

Product #: 323822

Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

IATA

UN number	UN1950
UN proper shipping name	AEROSOLS, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable
Environmental hazards	Yes
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed
Cargo aircraft only	Allowed
Packaging exceptions	LTD QTY

IMDG

UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable
Environmental hazards	
Marine pollutant	Yes
EmS	F-D, S-U

Safety Data Sheet

Material Name: 14 oz Hardcast Edge Sealer LT 12pk

Product #: 323822

Special precautions for user

Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.

Packaging exceptions

LTD QTY

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

US DOT



IATA; IMDG



Marine pollutant



General Information

IMDG Regulated Marine Pollutant.

Section 15 - REGULATORY INFORMATION

U.S. Federal Regulations



Safety Data Sheet

Material Name: 14 oz Hardcast Edge Sealer LT 12pk

Product #: 323822

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS-67-64-1) Listed

Toluene (CAS 108-88-3) Listed

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986

(SARA) Hazard categories:

Immediate Hazard – Yes

Delayed Hazard – Yes

Fire Hazard – Yes

Pressure Hazard – No

Reactivity Hazard – No

SARA 302 Extremely hazardous substance

Chemical name	CAS #	Reportable quantity	Threshold planning quantity, lower value	Threshold planning quantity, upper value
Phenol	108-95-2	1000	500 lbs	10000 lbs

SARA 311/312 Hazardous

No chemical

SARA 313 (TRI reporting)

Chemical name	CAS #	% by wt.
Toluene	108-88-3	2.5 - 10
Ethyl Benzene	100-41-4	0.01 - 0.1
Naphthalene	91-20-3	0.01 - 0.1
Styrene	100-42-5	0.01 - 0.1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Toluene (CAS 108-88-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Dimethyl Ether (CAS 115-10-6)

Propane (CAS 74-98-6)

Safe Drinking Water Act (SDWA)

Not regulated.

Safety Data Sheet

Material Name: 14 oz Hardcast Edge Sealer LT 12pk

Product #: 323822

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1) 6532
Toluene (CAS 108-88-3) 6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 % WV
Toluene (CAS 108-88-3) 35 % WV

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1) 6532
Toluene (CAS 108-88-3) 594

U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	MA	NJ	PA	RI	CA
2,2-Dimethylbutane	75-83-2	Yes	Yes	Yes	No	No
2,3-Dimethylbutane	79-29-8	Yes	Yes	Yes	No	No
2-Methylpentane	107-83-5	Yes	Yes	Yes	No	No
3-Methylpentane	96-14-0	Yes	No	Yes	No	No
Acetone	67-64-1	Yes	Yes	Yes	Yes	No
Dimethyl Ether	115-10-6	Yes	Yes	Yes	Yes	No
Propane	74-98-6	Yes	Yes	Yes	Yes	No
Toluene	108-88-3	Yes	Yes	Yes	Yes	Yes

The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

WARNING! This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Ethyl Benzene (CAS 100-41-4) Listed: June 11, 2004
Naphthalene (CAS 91-20-3) Listed: April 19, 2002

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Toluene (CAS 108-88-3) Listed: January 1, 1991

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

Toluene (CAS 108-88-3) Listed: August 7, 2009

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes

Safety Data Sheet

Material Name: 14 oz Hardcast Edge Sealer LT 12pk

Product #: 323822

Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Section 16 - OTHER INFORMATION

Summary of Changes

Revision Date: June 1, 2018

Revision Note: General Update

Disclaimer:

The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision Information

Product and Company Identification: Alternate Trade Names

GHS: Classification