

Safety Data Sheet

Material Name: Seal Tack Black**Product #: 5-gallon 318902
4 X 1 gallon 318903**

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name

Seal Tack Black

Synonyms

Water-Based Vapor Barrier/ Lagging Insulation Sealant

Chemical Family

Sealant

Product UseCoating for foam insulation; Sealer for cut ends of fibrous glass duct liner and wrapped duct insulation;
Vapor barrier for liquid chiller; Steam piping insulation applications**Restrictions on Use**

For use in industrial installations only.

Manufacturer InformationCarlisle HVAC Products
900 Hensley Lane
Wylie, TX 75098
www.carlislehvac.com**Medical Emergency:****CHEMTREC (USA): (800) 424-9300**

MSDS Assistance – 972-442-6545

Technical Assistance – 888-229-2199

Customer Service – 888-229-0199– 888-229-0199

Section 2 - HAZARDS IDENTIFICATION

Classification in accordance with paragraph (d) of 29 CFR 1910.1200.

Reproductive Toxicity - Category 1B

GHS Label Elements**Symbol(s)****Signal Word**

Danger

Hazard Statement(s)

Safety Data Sheet

Material Name: Seal Tack Black

**Product #: 5-gallon 318902
4 X 1 gallon 318903**

May damage fertility or the unborn child

Precautionary Statement(s)

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection

Response

If exposed or concerned: Get medical advice/attention

Storage

Store locked up

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations

Other Hazards

No additional information available.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent
Trade Secret	De-foaming agent	0.1-1
Trade Secret	Nonylphenol polyethylene glycol ether	0.1-1
Mixture	Polymer, ethyl acrylate and methacrylic acid	1-5
7664-41-7	Ammonia	0.1-1
1333-86-4	Carbon black	0.1-1
Mixture	Polycarboxylate salt	0.1-1
107-21-1	Ethylene glycol	0.36
Mixture	1,2-Benzisothiazolin-3-one mixture	0.1-1
Trade Secret	Aluminum trihydroxide	7-13
1317-65-3	Limestone	1-5
Mixture	Carbamic acid mixture	0.1-1
Trade Secret	Acrylic resin	1-5

Safety Data Sheet

Material Name: Seal Tack Black

**Product #: 5-gallon 318902
4 X 1 gallon 318903**

Section 4 - FIRST AID MEASURES

Description of Necessary Measures

If exposed or concerned: Call a POISON CENTER or doctor/physician.

Inhalation

Remove person to fresh air and keep comfortable for breathing. Get medical attention, if needed.

Skin

Wash exposed skin with soap and water. Remove contaminated clothing and wash it before reuse. If skin irritation occurs, get medical advice/attention.

Eyes

Rinse cautiously with water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

Ingestion

Do NOT induce vomiting. If swallowed, get medical attention.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically and supportively.

Most Important Symptoms/Effects

Acute

May cause mild eye irritation.

Delayed

May damage fertility or the unborn child.

Note to Physicians

Contains: ethylene glycol, ammonia.

Section 5 - FIRE FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Use carbon dioxide, regular dry chemical, regular foam or water.

Unsuitable Extinguishing Media

None reported.

Special Hazards Arising from the Chemical

Slight fire hazard. Sealed containers may rupture or explode if exposed to heat.

Hazardous Combustion Products

Oxides of carbon, oxides of nitrogen, hydrocarbons

Safety Data Sheet

Material Name: Seal Tack Black

**Product #: 5-gallon 318902
4 X 1 gallon 318903**

Special Protective Equipment and Precautions for Firefighters

Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

Fire Fighting Measures

Remove product from area of fire. Stay upwind and keep out of low areas.

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8.

Methods and Materials for Containment and Cleaning Up

Absorb with earth, sand or other non-combustible material and transfer to container. Dike for later disposal. Dispose in accordance with all applicable regulations.

Environmental Precautions

Avoid release to the environment.

Section 7 - HANDLING AND STORAGE

Precautions for Safe Handling

This product contains crystalline silica, which is a known carcinogen, including Carbon Black: Do not grind or sand, Do not evaporate or distill to dryness. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse. KEEP OUT OF REACH OF CHILDREN.

Conditions for Safe Storage, Including any Incompatibilities

Store locked up

Store in a well-ventilated place. Store above 0 C. Store below 45 C. When not in use, keep containers tightly closed. Do not cut, puncture, or weld on or near this container. Keep away from incompatible materials.

Incompatible Materials

Strong acids, strong oxidizing agents

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

Ammonia	7664-41-7
---------	-----------

Safety Data Sheet

Material Name: Seal Tack Black

**Product #: 5-gallon 318902
4 X 1 gallon 318903**

ACGIH:	25 ppm TWA	35 ppm STEL
NIOSH:	25 ppm TWA; 18 mg/m ³ TWA	35 ppm STEL; 27 mg/m ³ STEL
	300 ppm IDLH	
Europe:	20 ppm TWA; 14 mg/m ³ TWA	50 ppm STEL; 36 mg/m ³ STEL
OSHA (US):	50 ppm TWA; 35 mg/m ³ TWA	
Mexico:	25 ppm TWA LMPE-PPT; 18 mg/m ³ TWA LMPE-PPT	
	35 ppm STEL [LMPE-CT]; 27 mg/m ³ STEL [LMPE-CT]	
Carbon black	1333-86-4	
ACGIH:	3 mg/m ³ TWA inhalable fraction	
NIOSH:	3.5 mg/m ³ TWA; 0.1 mg/m ³ TWA (Carbon black in presence of Polycyclic aromatic hydrocarbons) as PAH	
	1750 mg/m ³ IDLH	
OSHA (US):	3.5 mg/m ³ TWA	
Mexico:	3.5 mg/m ³ TWA LMPE-PPT	7 mg/m ³ STEL [LMPE-CT]
Ethylene glycol	107-21-1	
ACGIH:	100 mg/m ³ Ceiling aerosol only	
Europe:	20 ppm TWA; 52 mg/m ³ TWA	40 ppm STEL; 104 mg/m ³ STEL
	Possibility of significant uptake through the skin	
Mexico:	100 mg/m ³ Ceiling aerosol	
Limestone	1317-65-3	
NIOSH:	10 mg/m ³ TWA total dust; 5 mg/m ³ TWA respirable dust	
OSHA (US):	15 mg/m ³ TWA total dust; 5 mg/m ³ TWA respirable fraction	
Mexico:	10 mg/m ³ TWA LMPE-PPT	20 mg/m ³ STEL [LMPE-CT]

Biological limit value

There are no biological limit values for any of this product's components.

Safety Data Sheet

Material Name: Seal Tack Black

Product #: 5-gallon 318902
4 X 1 gallon 318903

Engineering Controls

Provide adequate ventilation. Ensure compliance with applicable exposure limits.

Individual Protection Measures, such as Personal Protective Equipment

Eye/face protection

Wear splash resistant safety goggles. Provide an emergency eye wash fountain in the immediate work area.

Skin Protection

Wear appropriate work clothing.

Respiratory Protection

A NIOSH approved air-purifying respirator with an appropriate cartridge or canister may be appropriate under certain circumstances where airborne concentrations are expected to exceed exposure limits.

Glove Recommendations

Wear protective gloves. Recommended material: Hycron(R), neoprene, nitrile.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Gray to black latex	Physical State	Liquid
Odor	Slight, ammonia	Color	gray to black
Odor Threshold	Not available	pH	9 - 9.5
Melting Point	Not available	Boiling Point	212 °F
Freezing point	Not available	Evaporation Rate	42 - 46 % volatile
Boiling Point Range	Not available	Flammability (solid, gas)	Not available
Autoignition	Not available	Flash Point	Not available
Lower Explosive Limit	Not available	Decomposition	Not available
Upper Explosive Limit	Not available	Vapor Pressure	17 mmHg (@ 20 °C)
Vapor Density (air=1)	<1	Specific Gravity (water=1)	Not available
Water Solubility	Soluble	Partition coefficient: n-octanol/water	Not available
Viscosity	>20 Kcps (@ 77 °F)	Solubility (Other)	Not available
Density	1.16 (relative)	VOC	13 g/L (water excluded)

Safety Data Sheet

Material Name: Seal Tack Black

**Product #: 5-gallon 318902
4 X 1 gallon 318903**

Other Information

No additional information available.

Section 10 - STABILITY AND REACTIVITY

Reactivity

No reactivity hazard is expected.

Chemical Stability

Stable under normal conditions of use.

Possibility of Hazardous Reactions

Hazardous polymerization will not occur.

Conditions to Avoid

Avoid heat, flames, sparks and other sources of ignition. Avoid contact with incompatible materials.

Incompatible Materials

Strong acids, strong oxidizing agents

Hazardous decomposition products

Oxides of carbon, oxides of nitrogen, hydrocarbons

Section 11 - TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation

High concentrations may cause irritation of the respiratory tract.

Skin Contact

May cause mild skin irritation.

Eye Contact

May cause mild eye irritation.

Ingestion

Large doses may cause central nervous system stimulation followed by depression.

Acute and Chronic Toxicity

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Ethylene-vinyl acetate copolymer (Trade Secret)
Oral LD50 Rat >2000 mg/kg

De-foaming agent (Trade Secret)
Oral LD50 >2000 mg/kg

Safety Data Sheet

Material Name: Seal Tack Black

**Product #: 5-gallon 318902
4 X 1 gallon 318903**

Nonylphenol polyethylene glycol ether (Trade Secret)
Oral LD50 Rat 2780 mg/kg

Chlorinated paraffins (Trade Secret)
Oral L 50 Rat >4 g/kg

Polymer, ethyl acrylate and methacrylic acid (Mixture)
Oral LD50 Rat >5000 mg/kg
Dermal LD50 Rabbit >5000 mg/kg

Ammonia (7664-41-7)
Oral LD50 Rat 350 mg/kg
Inhalation LC50 Rat 2000 ppm 4 h

Ethoxylated nonylphenol (Trade Secret)
Oral LD50 Rat 1310 mg/kg
Dermal LD50 Rabbit 1780 µL/kg

Carbon black (1333-86-4)
Oral LD50 Rat 120 mg/kg (Intravenous)

Hydrocarbon defoamer (Trade Secret)
Oral LD50 Rat >5 g/kg

Polycarboxylate salt (Mixture)
Oral LD50 Rat >5000 mg/kg
Dermal LD50 Rabbit >2000 mg/kg

Ethylene glycol (107-21-1)
Oral LD50 Rat 4700 mg/kg
Dermal LD50 Rat 10600 mg/kg
Inhalation LC50 Rat >200 mg/m³ vapor 4 hr

1,2-Benzisothiazolin-3-one mixture (Mixture)
Oral LD50 Rat 2342 mg/kg
Dermal LD50 Rabbit >5000 mg/kg
Inhalation LC50 Rat 900 mg/m³ 4 hr

Aluminum trihydroxide (Trade Secret)
Oral LD50 Rat >5000 mg/kg

Limestone (1317-65-3)
Oral LD50 Rat 6450 mg/kg

Carbamic acid mixture (Mixture)

Safety Data Sheet

Material Name: Seal Tack Black**Product #: 5-gallon 318902
4 X 1 gallon 318903**

Oral LD50 Rat >2000 mg/kg
Dermal LD50 Rabbit >2000 mg/kg
Inhalation LC50 Rat >2.04 mg/L 4 hr

Immediate Effects

May cause mild eye irritation.

Delayed Effects

May damage fertility or the unborn child.

Irritation/Corrosivity Data

May cause mild eye irritation.

Respiratory Sensitization

No data available.

Dermal Sensitization

No data available.

Component Carcinogenicity

Chlorinated paraffins	Trade Secret
IARC:	Monograph 48 [1990] (Group 2B (possibly carcinogenic to humans))
DFG:	Category 3B (could be carcinogenic for man)
OSHA:	Present
Carbon black	1333-86-4
ACGIH:	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans
IARC:	Monograph 93 [2010]; Monograph 65 [1996] (Group 2B (possibly carcinogenic to humans))
DFG:	Category 3B (could be carcinogenic for man, inhalable fraction)
OSHA:	Present
Ethylene glycol	107-21-1
ACGIH:	A4 - Not Classifiable as a Human Carcinogen

Germ Cell Mutagenicity

No data available.

Reproductive Toxicity

May damage fertility or the unborn child.

Safety Data Sheet

Material Name: Seal Tack Black

**Product #: 5-gallon 318902
4 X 1 gallon 318903**

Specific Target Organ Toxicity - Single Exposure

No target organs identified.

Specific Target Organ Toxicity - Repeated Exposure

No target organs identified.

Aspiration hazard

No data available.

Medical Conditions Aggravated by Exposure

No data available.

Additional Data

No additional information available.

Section 12 - ECOLOGICAL INFORMATION

Ecotoxicity

Avoid release to the environment.

Component Analysis - Aquatic Toxicity

Ethylene-vinyl acetate copolymer	Trade Secret
Fish:	LC50 96 hr Cyprinus carpio >1000 mg/L
Chlorinated paraffins	Trade Secret
Fish:	LC50 96 h Lepomis macrochirus >300 mg/L [static]; LC50 96 h Oncorhynchus mykiss >0.0109 mg/L [flow-through]; LC50 96 h Oncorhynchus mykiss 94.5 - 271 mg/L [static]; LC50 96 h Lepomis macrochirus >0.1 mg/L [flow-through]; LC50 96 h Pimephales promelas >100 mg/L [static]
Invertebrate:	EC50 48 hr Daphnia magna 0.0059 mg/L
Polymer, ethyl acrylate and methacrylic acid	Mixture
Fish:	LC50 96 hr Pimephales promelas >1000 mg/L
Invertebrate:	EC50 48 hr Daphnia magna >1000 mg/L
Ammonia	7664-41-7

Safety Data Sheet

Material Name: Seal Tack Black

**Product #: 5-gallon 318902
4 X 1 gallon 318903**

Fish:	LC50 96 h Cyprinus carpio 0.44 mg/L; LC50 96 h Lepomis macrochirus 0.26 - 4.6 mg/L; LC50 96 h Lepomis macrochirus 1.17 mg/L [flow-through]; LC50 96 h Pimephales promelas 0.73 - 2.35 mg/L; LC50 96 h Pimephales promelas 5.9 mg/L [static]; LC50 96 h Poecilia reticulata >1.5 mg/L; LC50 96 h Poecilia reticulata 1.19 mg/L [static]
Invertebrate:	LC50 48 h Daphnia magna 25.4 mg/L IUCLID
Hydrocarbon defoamer	Trade Secret
Fish:	LC50 96 h Oncorhynchus mykiss >5000 mg/L
Invertebrate:	EC50 48 h Daphnia magna >1000 mg/L IUCLID
Ethylene glycol	107-21-1
Fish:	LC50 96 h Oncorhynchus mykiss 41000 mg/L; LC50 96 h Oncorhynchus mykiss 14 - 18 mL/L [static]; LC50 96 h Lepomis macrochirus 27540 mg/L [static]; LC50 96 h Oncorhynchus mykiss 40761 mg/L [static]; LC50 96 h Pimephales promelas 40000 - 60000 mg/L [static]; LC50 96 h Poecilia reticulata 16000 mg/L [static]
Algae:	EC50 96 h Pseudokirchneriella subcapitata 6500 - 13000 mg/L IUCLID
Invertebrate:	EC50 48 h Daphnia magna 46300 mg/L IUCLID
1,2-Benzisothiazolin-3-one mixture	Mixture
Fish:	LC50 96 hr Rainbow trout 21 mg/L [flow-through]
Invertebrate:	EC50 48 hr Daphnia magna 26 mg/L

Persistence and Degradability

No information available for the product.

Bioaccumulative Potential

No information available for the product.

Mobility

No information available for the product.

Other Toxicity

No additional information available.

Safety Data Sheet

Material Name: Seal Tack Black

Product #: 5-gallon 318902
4 X 1 gallon 318903

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of contents/container in accordance with local/regional/national/international regulations.

Section 14 - TRANSPORT INFORMATION

US DOT Information:

UN/NA #: Not regulated

IATA Information:

UN#: Not regulated

TDG Information:

UN#: Not regulated

Section 15 - REGULATORY INFORMATION

U.S. Federal Regulations

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), and/or require an OSHA process safety plan.

Ammonia	7664-41-7
SARA 302:	500 lb TPQ
SARA 313:	1 % de minimis concentration (includes anhydrous Ammonia and aqueous Ammonia from water dissociable Ammonium salts and other sources, 10% of total aqueous Ammonia is reportable under this listing)
CERCLA:	100 lb final RQ; 45.4 kg final RQ
OSHA (safety):	10000 lb TQ anhydrous); 15000 lb TQ solution, >44% Ammonia by weight)
SARA 304:	100 lb EPCRA RQ
Ethoxylated nonylphenol	Trade Secret

Safety Data Sheet

Material Name: Seal Tack Black**Product #: 5-gallon 318902
4 X 1 gallon 318903**

TSCA 12b:	Section 5 , 1 % de minimus concentration
Ethylene glycol	107-21-1
SARA 313:	1 % de minimis concentration
CERCLA:	5000 lb final RQ; 2270 kg final RQ
Carbamic acid mixture	Mixture
CERCLA:	10 lb final RQ; 4.54 kg final RQ

SARA Section 311/312 (40 CFR 370 Subparts B and C)**Acute Health:** Yes **Chronic Health:** Yes **Fire:** No **Pressure:** No **Reactivity:** No**U.S. State Regulations**

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
Chlorinated paraffins	Trade Secret	No	Yes	No	No	No
Ammonia	7664-41-7	Yes	Yes	Yes	Yes	Yes
Carbon black	1333-86-4	Yes	Yes	Yes	Yes	Yes
Ethylene glycol	107-21-1	Yes	Yes	Yes	Yes	Yes
Limestone	1317-65-3	No	Yes	Yes	Yes	Yes
Carbamic acid mixture	Mixture	No	No	No	Yes	No

The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):**WARNING!** This product contains a chemical known to the state of California to cause cancer

Carbon black	1333-86-4
Carc:	carcinogen , 2/21/2003 (airborne, unbound particles of respirable size)

Canadian WHMIS Ingredient Disclosure List (IDL)

Components of this material have been checked against the Canadian WHMIS Ingredients Disclosure List. The List is composed of chemicals which must be identified on MSDSs if they are included in products which meet WHMIS criteria specified in the Controlled Products Regulations and are present above the threshold limits listed on the IDL

Ammonia	7664-41-7
	1 %

Safety Data Sheet

Material Name: Seal Tack Black

**Product #: 5-gallon 318902
4 X 1 gallon 318903**

Carbon black	1333-86-4
	1 %
Ethylene glycol	107-21-1
	1 %

Component Analysis - Inventory

Ethylene-vinyl acetate copolymer (Trade Secret)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	ELN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Nonylphenol polyethylene glycol ether (Trade Secret)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	No	Yes	Yes	Yes	No	Yes	No	Yes	Yes	No

Chlorinated paraffins (Trade Secret)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Polymer, ethyl acrylate and methacrylic acid (Mixture)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	No	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Ammonia (7664-41-7)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Ethoxylated nonylphenol (Trade Secret)

Safety Data Sheet

Material Name: Seal Tack Black

**Product #: 5-gallon 318902
4 X 1 gallon 318903**

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	No	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Carbon black (1333-86-4)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Hydrocarbon defoamer (Trade Secret)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	No	No	Yes	No	Yes	Yes	Yes

Ethylene glycol (107-21-1)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

1,2-Benzisothiazolin-3-one mixture (Mixture)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Aluminum trihydroxide (Trade Secret)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Limestone (1317-65-3)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	NSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Carbamic acid mixture (Mixture)

Safety Data Sheet

Material Name: Seal Tack Black**Product #: 5-gallon 318902
4 X 1 gallon 318903**

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes

Section 16 - OTHER INFORMATION

HMIS Rating

Health: 1* Fire: 0 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

NFPA Ratings

Health: 1 Fire: 0 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Summary of Changes

Revision Date: June 1, 2018

Revision Note: General Update

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States.

Other Information

Safety Data Sheet

Material Name: Seal Tack Black

**Product #: 5-gallon 318902
4 X 1 gallon 318903**

Disclaimer:

The information contained herein is based upon data and information available to us, and reflects our best professional judgment. This product may be formulated in part with components purchased from other companies. In many instances, especially when proprietary or trade secret materials are used, CCWI Company must rely upon the hazard evaluation of such components submitted by that product's manufacturer or importer. No warranty of merchantability, fitness for any use, or any other warranty is expressed or implied regarding the accuracy of such data or information. The results to be obtained from the use thereof, or that any such use does not infringe any patent, since the information contained herein may be applied under conditions of use beyond our control and with which we may be unfamiliar, we do not assume responsibility for the results of such application. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular use