



## OVERVIEW

Super Tack Travel-Tack is a self-contained, highly aggressive, instant-tacking portable spray system that is engineered to deliver a web spray pattern. Its portability, limited equipment clean-up, and low equipment cost make this adhesive ideal for shop or field use.

## PART NUMBERS

333270	(1) #40 Cylinder
--------	------------------

## SPECIFICATION/STANDARDS COMPLIANCE

Property	Method	Results
Duct Thermal Insulation	ASTM C916	Pass
VOC Limitations	Ozone Transport Commission (OTC) with Exception to CT	Pass
Flame	ASTM E84	5
Smoke	ASTM E84	20

## APPLICATION

Temperature	60°F to 90°F (15.5°C to 32.2°C) (Keep at 70°F for optimum performance. If cylinder temperature falls below 70°F, move it to a warm area until optimum performance is achieved.)
Method	Apply according to SMACNA specifications and local codes.
Preparation	Surface must be dry and free of dirt, oil, moisture and grease.
Rate	16-oz per minute
Clean Up	Low-VOC UN-TACK™ Cleaner/Adhesive Remover, petroleum solvents or mineral spirits

## TYPICAL PROPERTIES AND CHARACTERISTICS

Color	Green
Consistency	Aerosol spray
Spray Pattern	Variable web
Odor	Solvent like
Base	Synthetic Rubber
Vapor Pressure	70 psi
Solvent	Methylene Chloride
Approx. Coverage	125 sq ft/lb of adhesive
Initial Bonding Time	Immediate
Dry Time	3-4 minutes
Adhesion	Excellent
Service Temperature	-40°F to 200°F (4.4°C to 93.3°C)
Flammability	Flammable when wet. Nonflammable when dry.
Water Resistance	Excellent
Mildew Resistance	Good
VOC	380 g/l

## PRECAUTIONS

- Do not expose to heat or store above 100°F (38°C)
- Do not puncture or incinerate.
- Canister is not re-fillable. When empty, dispose by following local code requirements.
- Review Safety Data Sheet for safety information prior to use.

**For Industrial Professional Use Only.**

## STORAGE

Temperature	60°F to 95°F (15°C to 35°C)
Shelf Life	One year (unopened)