



PART NUMBERS

304182	1 Case w/ (24) 2" x 50' Rolls
304183	1 Case w/ (16) 3" x 50' Rolls
304184	1 Case w/ (12) 4" x 50' Rolls
304185	1 Case w/ (8) 6" x 50' Rolls
304186	1 Case w/(4) 9" x 50' Rolls
304181	1 Case w/ (4) 12" x 50' Rolls

TECHNICAL DATA

Appearance	Black, non-gloss
Backing	High density, water resistant polyethylene
Adhesive	THE GRAY MATTER™, Elastomeric Modified Butyl Rubber
Thickness	30 mils
Peel Strength	≥10 lbs. per linear inch
Tensile Strength	4.5 lbs/inch, ASTM D1970
Elongation	≥700%, ASTM D1970
Flexibility (low-temp)	Passes, no cracking
Bonding Time	Immediate, aggressive grip, water tight after one hour set time. Full bond within 24 hours
Operating Temperature	-20°F to 180°F (-28.9°C to 82.2°C)
Water Resistance	Excellent after set time. Surface must be clean and dry before application.

BRT-801 is a black, water resistant, hip and ridge sealant for use under tile and roof applications. BRT-801 has an aggressive grip, superior long-term adhesion and stays flexible during application, assuring immediate sealing on contact. Providing leak-proof results, this butyl adhesive/sealant is asphalt and solvent free. BRT-801 is also reverse-rolled for easy, fast application.

APPLICATION

Preparation	Clean surface – removing dust, dirt, oil and moisture. Peel off few inches of release liner.
Temperature	35°F to 110°F (1.7°C to 44°C)
Method	Position the product precisely. Product is not repositionable. DO NOT STRETCH. Remove the release liner and press down firmly starting at center and working toward outside edge while removing trapped air. Edges shall be firmly adhered to the substrate without opening or fishmouths. Roll surfaces to maximize adhesive.

STORAGE

Temperature	35°F to 110°F (1.7°C to 44°C)
Shelf Life	24 months (unopened)
Flammability	Non-flammable (contains no Asbestos, CFC or PCB)

PRECAUTIONS

Surfaces must be clean and free of moisture and contamination. Do not apply this product where temperatures exceed 200°F. Do not stretch this product during application. Keep out of the reach of children. DO NOT use where acidic or alkaline chemicals are present (i.e., lab fume hood, vents, etc.)

For Industrial Professional Use Only.